

Telehandler / Zoom Boom

Used Telehandler Orange - Telehandlers have numerous names including a teleporter, Cherry picker, telescopic handler or boom lift. This industrial machine is commonly used in a variety of industries and in agriculture. Similar to a crane and a forklift as it has a boom allowing it to extend forwards and upwards. Many different attachments can be used at the end of the articulating boom to facilitate a wide number of jobs. Different attachments such as a bucket, pallet forks, a muck grab or a winch can help the machine complete many jobs. The main telehandler attachment is the pallet forks. Pallet forks enable the operator to move loads to and from a variety of locations that would otherwise be considered unreachable with a standard forklift. These machines enable cargo pallets to be unloaded and loaded from a trailer and placed on rooftops, racking or other high and hard to access locations. Typically, high locations would traditionally require a crane; however, telehandlers can facilitate these tasks easily and efficiently. It isn't always practical or affordable to rely on a crane or secondary machinery to complete the job. Within agriculture, the bucket or bucket grab is among the most popular attachments. Relocating items from hard to reach areas that cannot rely on a wheeled loader or a backhoe loader give telehandlers a significant advantage. Telehandlers can directly access trailer units with high sides, hoppers or applications that would typically need a conveyor or loading ramp. Using one machine to finish numerous jobs saves storage space, money and time. Telehandler units often work together with a crane jib. Numerous attachments can be utilized including power booms, grain buckets, dirt buckets and rotators. The agricultural models can use three-point linkage and power take-off to make telehandlers multi-tasking. However, the main advantage of the telehandler is additionally its' largest limitation. The boom acts as a lever when it extends or raises with heavy loads. Despite significant counterweights in the rear, the telehandler can be subject to instability at times, decreasing the lifting capacity as the working radius or distance between the center of the load and the front of the wheels increases. When a telehandler functions as a single boom loader (as opposed to twin arms) and carrying a heavy load, there can be a potential for weakness even in the best designs. For instance, a telehandler with a five thousand pound capacity may be capable of safely lifting as little as four hundred pounds fully extended with a low boom angle with a retracted boom. Raising the same piece of equipment 70 degrees could allow this machine with a five thousand pound lift capability and retracted boom to support up to ten thousand pounds. Monitoring the angle, weight and boom height, there are load charts on this equipment to outline which tasks can be safely conducted. Updated telehandler models have computers and sensors. The operator is warned and even cut off further control input once the limits of the telehandler are surpassed. Front stabilizers that enhance the lifting capacity of the machine while stationary can make a huge difference. A stabilizing rotary joint between the upper and lower frames may be called a mobile crane that can use a bucket. Compact telehandler models are available in a variety of different weights, reach, sizes and boom designs. If the machine weighs in at eleven thousand pounds or less, it can be part of the compact category. Compact units have a two-stage boom compared to larger machines that feature three or four boom designs. A low pivot boom ensures better operator visibility for transporting loads on compact units. Compact models are skinnier and have thinner dimensions. The compact units offer a reach capacity between thirteen to twenty feet and a lifting capacity ranging from five thousand to seven thousand pounds. These versatile machines make the compact telehandler extremely popular. This machine can be utilized for carrying tools or as a pick and place unit. It is commonly utilized in spaces that are tight and cramped. Residential applications are common as contractors relish their useful nature with framing applications and where height restrictions come into play. These units can be useful for accessing internal building locations. Compact telehandlers are used in many applications including nurseries, erecting steel, multi-story construction, masonry, strip malls, garages and similar jobs. Farming and agri-business applications often rely on telehandlers to accomplish many tasks. Telehandlers can be found with two and four-wheel drive and crab

steering capabilities. The unit can travel over longer ranges at higher speeds with two-wheel drive, making it ideal for moving throughout job sites. Four-wheel drive units can travel over harder terrain while offering a tighter turning radius. Crab steering enhances the units' maneuverability while allowing each set of wheels to move forty-five degrees to the right or left. There are a variety of cab interior options available for compact telehandlers. On entry-level models, there is a rollover cage for added safety. Newer units come with windshield wipers, a defroster, a heater and a totally enclosed cab. All compact telehandler cabs are spacious to accommodate the operator as comfortable as possible. Extra amenities including air conditioning, satellite radio, suspension seats, tilt steering and cup holders are available. Many high-pressure hydraulics and high-flow auxiliary hydraulics operate the numerous attachments. The different attachments allow the machine to be capable of many options. All of these attachments enable the machine to conduct a variety of jobs. Ground engaging work is often completed by compact units. It is simple to transform a compact telehandler into a mini excavator with a bucket attachment. There are popular attachments including brooms for sweeping, truss booms for extended reach, side-shifting and rotating fork carriages, heavy and light-duty buckets, augers for planting trees or digging holes and many items. Skid steer attachments are being manufactured for certain compact telehandler designs for even more versatility.